

PRODUCT DATA SHEET

7861 AIRPORT HIGHWAY, PENNSAUKEN, NJ 08109 (800)346-4378 Sales@seminolewire.com

Part Number 1318 **Description** 18AWG Solid CCS, Ladder Line

Application Twin-lead cable is a two-conductor flat cable used as a transmission line to carry radio frequency (RF) signals. Mainly used

to connect radio transmitters and receivers to their antennas.

Compatibility

Approvals/Ratings **ITU-R Regulations**

Construction & Specifications

Materials	Description	Specification / Standard
Conductor	Copper Clad Steel	18AWG (ASTM)
Dielectric		
Stranding	1	0.0403in (1.024mm)
Insulation	Linear Low Density Polyethylene	0.020 in nom wall
Number of conductors	2	
Number of pairs		
Pair Lay Length		
Cable Lay Length		
Shield		
Drain		
Jacket Insulation		
Overall Cable Diameter		0.06E v 0.020 in

Overall Cable Diameter 0.065 x 0.930 in

Cross-section diagram (not to scale)



Electrical & Environmental Properties



European Directive 2011/65/EU Compliant

ALL COMPONENTS REACH COMPLIANT Registration, Evaluation and Authorisation of Chemicals

Temperature Rating Sunlight Resistant Voltage Rating **Operating Voltage**

Capacitance Between Conductors @ 1 KHz Capacitance Between Conductor(s) to Shield @ 1KHz DC Resistance per Conductor @ 20°C **Impedance** Velocity of Propagation Attenuation Tensile Strength Elongation

-40°C to +60°C Yes 300 (V) 9.71Ω 450 Ω 90.2% ----(db/1000ft)

----(lbs) ----(%)

Miscellaneous Information

Insulation Color* Black Pairing Combination* Jacket Color*

JSC WIRE & CABLE #1318 18 AWG SOLID CCS ROHS MADE IN THE USA <SEQ FT> Print*

Weight ~22 lbs./ 1000 ft.

> Type* & Size* Packaging* & Pallets* 100, 500 Ft. Plastic Spool

Plain Corrugated Carton, Domestic Plywood Pallet 1000-4000 Ft. Plywood Reel Plain Corrugated Wrap, Domestic Plywood Pallet

Warranties & Disclaimer

Put Up Length*

*Items can be customized. The customer accepts all factory lengths and +/- 10 percent of total order required.

All product data presented is for informational purposes only and does not create a binding obligation or liability on Seminole and JSC Wire and Cable Co Inc or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to standard terms and conditions. Seminole and JSC Wire and Cable Co Inc disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Seminole and JSC Wire and Cable Co Inc. Any information contained herein shall not be disclosed to any party without written consent of Seminole and JSC Wire and Cable Co Inc.

All products sold are warranted by company only to customers for: (i) resale; or (ii) use in business, government or original equipment manufacturer. Company warrants products against defects in materials and workmanship under normal use for a period of six months after the date of purchase from company, unless otherwise stated. Provided that company accepts the product for return during the limited warranty period, company may, at its option: (i) repair; (ii) replace; or (iii) refund the amount paid by customer. Customer must return the product to the appropriate company branch as designated by company, shipping costs prepaid. Company's repair, replacement, or refund of amounts paid by customer for the product, shall be customer's sole and exclusive remedy.