



**PRODUCT: N MALE CLAMP, STRAIGHT, 50 OHM, FOR RG-213/U, RG-214/U, RG-393/U**  
**PRODUCT CODE: E3660, Paratronic Oy**

Description	Material	Note	General information	
Contact pin	Brass	1	Dimensions in millimeters (mm), unless otherwise specified. RoHS compliant. Directive 2015/863 with exemption 6(c) Note, finish, plating thickness in micro-inches, $\mu\text{in}$ (minimum): 1. Gold (3) over nickel (50) over copper (50) 2. Nickel (100) over copper (50)	Impedance 50 ohm Frequency range DC - 6 GHz VSWR 1.2 max Insertion loss $\leq 0.3$ dB Insulator resistance $\geq 5$ G $\Omega$ Resistance, center contact $\leq 1.5$ m $\Omega$ , outer c. $\leq 0.25$ m $\Omega$ Test voltage 2500 V rms, working voltage 1400 V rms Power handling $\leq 700$ W @ 2 GHz
Insulator	PTFE	-		
Body, shell	Brass	2		
Braid clamp	Brass	2		
Ferrule	Brass	2		
Washer	Brass	2		
Pin 2	Brass	1		
Gaskets	Silicone	-		
Retainer ring	Phosphor bronze	-	IP67 when mated, if added suitable heatshrink with glue over rear body/cable, not included. IP40 unmated	



Cable stripping dimensions:



Title	Value
Drawing date	20.2.2023
Version	A
Website	www.paratronic.fi