

**RFA 1/2" COAXIAL CABLE**
**NK CODES**

RFA 1/2"-50  
 RFA 1/2"-50 BHF (UL) CATVR  
 RFA 1/2"-50 GHF Cca  
 RFA 1/2"-50 BHF Cca

NKRFA01200  
 NKRFA01204  
 NKRFA01211  
 NKRFA01212

**CONSTRUCTION**


|                 |   |           |           |
|-----------------|---|-----------|-----------|
| Inner conductor | Copper-clad aluminium wire  | Ø 4.8 mm  | (0.19 in) |
| Dielectric      | Cellular polyethylene   | Ø 12.1 mm | (0.48 in) |
| Outer conductor | Corrugated copper tube  | Ø 13.9 mm | (0.55 in) |
| Jacket          | See Jacketing Options table below   | Ø 16.0 mm | (0.63 in) |
| Marking         | Draka, cable type, CPR class, manufacture week, year, batch number and meter mark |           |           |

**ELECTRICAL CHARACTERISTICS at +20°C (+68°F)**

|   |                            |
|---|----------------------------|
| Characteristic impedance                              | 50 ± 1 Ω                   |
| Return loss 24 dB for 100 m cable with NKC connectors |                            |
| - 380 - 500   | MHz                        |
| - 790 - 960   | "                          |
| - 1710 - 1880   | "                          |
| - 1900 - 2170   | "                          |
| - 2490 - 2700   | "                          |
| - 3400 - 3600   | "                          |
| Other bands also available on request                 |                            |
| Bands according to customer's specifications          |                            |
| Attenuation   | See table                  |
| Velocity factor                                       | 0.88                       |
| Capacitance   | 76.1 pF/m (23.2 pF/ft)     |
| Inductance  | 0.19 µH/m (0.058 µH/ft)    |
| Maximum frequency                                     | 9500 MHz                   |
| Max power rating                                      | See table                  |
| Peak RF voltage rating                                | 1.80 kV                    |
| Peak power rating                                     | 31.8 kW                    |
| DC resistance   |                            |
| - Inner conductor                                     | 1.60 Ω/km (0.44 Ω/1000 ft) |
| - Outer conductor                                     | 2.28 Ω/km (0.69 Ω/1000 ft) |

**MECHANICAL CHARACTERISTICS**

|                             |             |                 |
|-----------------------------|-------------|-----------------|
| Weight                      | 0.25 kg/m   | (0.17 lb/ft)    |
| Maximum pulling force       | 1800 N      | (404 lb)        |
| Minimum bending radius      |             |                 |
| - Single bending            | 70 mm       | (2.8 in)        |
| - Repeated bending          | 120 mm      | (4.7 in)        |
| Operating temperature range | -55...+85°C | (-67...+185 °F) |
| Crush resistance            | 1.7 kg/mm   | (94 lb/in)      |
| Bending moment              | 3.8 Nm      | (2.8 lb-ft)     |
| Recommended clamp spacing   | 1.0 m       | (3.3 ft)        |

**JACKETING OPTIONS**

| TYPE                       | JACKET   | IEC 60754 - 1/-2<br>Halogen free, non corrosive | IEC 61034<br>low smoke emission | IEC 60332-3-24<br>fire retardant | CPR class  | UV retardancy | UL Rated | Min. installation temperature |
|----------------------------|--|---|---------------------------------|----------------------------------|------------|---------------|----------|-------------------------------|
| RFA 1/2"-50                | Black, halogen free polyethylene                         | yes   | no                              | no                               | no         | yes           | no       | -40°C (-40°F)                 |
| RFA 1/2"-50 GHF Cca        | Grey, halogen free fire retardant thermoplastic          | yes   | yes                             | yes                              | Cca-s1d1a1 | no            | no       | -20°C (-4°F)                  |
| RFA 1/2"-50 BHF Cca        | Black, halogen free fire retardant thermoplastic         | yes   | yes                             | yes                              | Cca-s1d1a1 | yes           | no       | -20°C (-4°F)                  |
| RFA 1/2"-50 BHF (UL) CATVR | Black, halogen free fire retardant UL Riser rated jacket | yes   | yes                             | Yes                              | no         | yes           | yes      | -20°C (-4°F)                  |

**RFA 1/2" COAXIAL CABLE**

| FREQUENCY<br>MHz | ATTENUATION<br>dB/100 m | ATTENUATION<br>dB/100 ft | POWER RATING<br>kW |
|------------------|-------------------------|--------------------------|--------------------|
| 10               | 0.664                   | 0.202                    | 12                 |
| 30               | 1.16                    | 0.353                    | 6.9                |
| 50               | 1.50                    | 0.458                    | 5.3                |
| 88               | 2.00                    | 0.611                    | 4.0                |
| 100              | 2.14                    | 0.652                    | 3.7                |
| 108              | 2.23                    | 0.679                    | 3.6                |
| 174              | 2.85                    | 0.868                    | 2.8                |
| 200              | 3.06                    | 0.933                    | 2.6                |
| 300              | 3.78                    | 1.15                     | 2.1                |
| 400              | 4.40                    | 1.34                     | 1.8                |
| 450              | 4.68                    | 1.43                     | 1.7                |
| 500              | 4.95                    | 1.51                     | 1.6                |
| 512              | 5.01                    | 1.53                     | 1.6                |
| 600              | 5.45                    | 1.66                     | 1.5                |
| 700              | 5.92                    | 1.81                     | 1.3                |
| 800              | 6.36                    | 1.94                     | 1.2                |
| 850              | 6.57                    | 2.00                     | 1.2                |
| 890              | 6.74                    | 2.05                     | 1.2                |
| 900              | 6.78                    | 2.07                     | 1.2                |
| 950              | 6.98                    | 2.13                     | 1.1                |
| 960              | 7.02                    | 2.14                     | 1.1                |
| 1000             | 7.18                    | 2.19                     | 1.1                |
| 1200             | 7.92                    | 2.41                     | 0.98               |
| 1400             | 8.62                    | 2.63                     | 0.91               |
| 1600             | 9.28                    | 2.83                     | 0.85               |
| 1800             | 9.90                    | 3.02                     | 0.79               |
| 1900             | 10.2                    | 3.11                     | 0.77               |
| 2000             | 10.5                    | 3.20                     | 0.75               |
| 2200             | 11.1                    | 3.37                     | 0.71               |
| 2400             | 11.6                    | 3.54                     | 0.68               |
| 2600             | 12.2                    | 3.71                     | 0.65               |
| 2800             | 12.7                    | 3.86                     | 0.62               |
| 3000             | 13.2                    | 4.02                     | 0.59               |
| 3400             | 14.2                    | 4.31                     | 0.55               |
| 6000             | 19.7                    | 6.00                     | 0.40               |
| 8800             | 23.4                    | 7.12                     | 0.33               |

Attenuation values are typical at ambient temperature +20°C (+68°F).  
Power rating ambient temperature +40°C (+104°F), inner conductor +100°C (+212°F).

**CODES FOR NKC CONNECTORS**

| CONNECTOR TYPE        | NK CODE    |
|-----------------------|------------|
| N male                | NKC1012300 |
| N female              | NKC1012400 |
| 7-16 male             | NKC1012100 |
| 7-16 female           | NKC1012200 |
| N male Right angle    | NKC1012600 |
| 7-16 male Right angle | NKC1012500 |

[PRODUCT CODE TABLE]

---

© PRYSMIAN GROUP 2017, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.